

Fabric Specification

| | | |
|---|---|---------------------------------------|
| Style # | BioDegradable PET 100% Yarn BD-627G11 | |
| Content | 100% Polyester | |
| Yarn Size | Warp: T75/72F | Fill: T150/144F |
| Construction | 145 X 80 ½ Twill | |
| Weave | ½ Twill | |
| Width | 58" | |
| Finish | Dyed, WR | |
| Coating | | |
| Fabric Weight | 125 GSM | 3.67 oz/sq.yd |
| Coating Weight | GSM | 0 oz/sq.yd |
| Total Weight | 125 GSM | 3.67 oz/sq.yd |
| Minimum Order Quantity | 12,000 yards / order 1,500 yards / color | |
| Fabric Performance | TEAR - ASTM D2261-96 (Tongue Tear) | Warp: lbs Fill : lbs |
| | TENSILE - ASTM D5034 : 1990 Grab 1" | Warp: lbs Fill : lbs |
| | TABER ABRASION - ASTM D3884 | |
| Country of Origin | Made in Taiwan | |
| <p>Please Note:</p> <p>The test results were provided to SRI by independent testing laboratories. They are provided for reference only. SRI makes no guarantee of the accuracy of these results. Manufacturers are responsible for testing products for their specific end use.</p> | | |